



Vertical Travel	Platform Width	Platform Length	Capacity (lbs.)	Raised Height	Lowered Height	Travel Time (sec.)	Wt. (lbs.)
36"	24"-48"	48"-72"	1,000	43"	7"	7	638
36"	24"-48"	48"-72"	2,000	43"	7"	11	738
36"	24"-48"	48"-72"	3,000	43"	7"	16	950
36"	24"-48"	48"-72"	4,000	43"	7"	22	980
36"	36"-48"	48"-72"	5,000	44"	8"	32	1029
36"	36"-48"	48"-72"	6,000	44"	8"	32	1108
36"	36"-48"	48"-72"	*8,000	44"	8"	15	1281
33"	40"-60"	48"-72"	*10,000	43"	10"	15	1438
33"	40"-60"	48"-72"	*12,000	43"	10"	15	1596
48"	24"-48"	64"-90"	1,000	55"	7"	11	755
48"	24"-48"	64"-90"	2,000	55"	7"	16	1176
48"	24"-48"	64"-90"	3,000	55"	7"	22	1250
48"	36"-48"	64"-96"	4,000	56"	8"	32	1271
48"	36"-48"	64"-96"	5,000	56"	8"	32	1339
48"	36"-48"	64"-96"	6,000	56"	8"	48	1420
48"	36"-48"	64"-96"	*8,000	56"	8"	15	1574
45"	40"-60"	64"-96"	*10,000	55"	10"	15	1659
45"	40"-60"	64"-96"	*12,000	55"	10"	20	1816
60"	24"-48"	84"-108"	1,000	67"	7"	16	1303
60"	24"-48"	84"-108"	2,000	67"	7"	14	1313
60"	24"-48"	84"-108"	3,000	67"	7"	16	1456
60"	48"-72"	96"-120"	*4,000	68"	8"	26	1848
60"	48"-72"	96"-120"	*5,000	68"	8"	26	1869
60"	48"-72"	96"-120"	*6,000	70"	10"	30	1890
60"	62"-72"	96"-120"	*8,000	70"	10"	30	3000
58"	62"-72"	96"-120"	*10,000	72"	14"	30	3498
58"	62"-72"	96"-120"	*12,000	72"	14"	30	3510
72"	24"-48"	102"-120"	1,000	79"	7"	12	2047
72"	24"-48"	102"-120"	2,000	79"	7"	16	2060
71"	48"-72"	120"-144"	*3,000	82"	11"	16	2089
71"	48"-72"	120"-144"	*4,000	82"	11"	26	3217
71"	48"-72"	120"-144"	*5,000	82"	11"	26	3675
70"	62"-72"	120"-144"	*6,000	82"	12"	30	3773
70"	62"-72"	120"-144"	*8,000	82"	12"	30	4007

\* DENOTES 6.5 HP 460V 3-PHASE (EXTERNALLY MOUNTED) OTHER Voltages AVAILABLE